



# PURELITE SLIM

PURELITE SLIM is something to admire before it has even been turned on. The slimmest and thinnest luminaire in the industry, it is a feat of imagination and innovation. But then a switch is flicked. And PURELITE SLIM becomes a sleek strip of pure, uninterrupted, exceptional light. Although its design is hard to comprehend, the luminaire itself is easy to install at every stage of a project. So, the possibilities are as wide as PURELITE SLIM is so elegantly thin.

## FEATURES

- Shadow-free lines of light, incl. illumination of the ceiling, timeless design
- Simple to integrate into the architecture thanks to its ultra-flat design: height of only 35 mm incl. control gear
- Available with integrated RUN diffuser (PURELITE SLIM D) or office-compatible RUN+ diffuser (PURELITE SLIM)
- Omnidirectional, with illumination of the ceiling, also available with direct lighting
- Batten luminaire range with a 2.5 cm design from standard, enables wall-to-wall planning

## TECHNICAL DATA

Luminous flux of luminaire	1600-3100 lm, Office 2150 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index (CRI)	≥ 80
Maintained luminous flux	L80 75'000 h
Glare value	Up to UGR < 19 $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$
Protection class	I
Ingress Protection	IP20
Photobiological safety	risk group 0, no risk

## SPECIFICATIONS

- Recessed ceiling, ceiling and wall mounting, pendant luminaire and channel lighting system
- Extremely good homogeneous direct illumination and all-round illumination
- support profiles made of natural anodised aluminium
- Clip-in LED batten with integrated through-wiring for quick and easy mounting
- LED batten luminaire replaceable on site
- High luminous efficacy of up to 150 lm/W

## APPLICATION AREAS



**Office & Education:** open-plan offices, individual offices, classrooms, meeting rooms, foyers and lobbies, circulation zones

**Retail & Hospitality:** hotels, restaurants

**Home & Living**




IP20 230V IK08  $\varnothing_{0.5m}$  850°C **A+**



### CEILING AND WALL MOUNTED LUMINAIRE PURELITE SLIM

System power	Luminous flux of luminaire	Colour temperature	Length	Ref. n°
11 W	1260 lm	4000 K	781 mm	2004.4887
11 W	1180 lm	3000 K	781 mm	2004.4884
14 W	1940 lm	4000 K	781 mm	2004.4893
14 W	1840 lm	3000 K	781 mm	2004.4890
15 W	2050 lm	4000 K	1231 mm	2004.4888
15 W	1940 lm	3000 K	1231 mm	2004.4885
21 W	3100 lm	4000 K	1231 mm	2004.4894
21 W	2950 lm	3000 K	1231 mm	2004.4891
18 W	2500 lm	4000 K	1531 mm	2004.4889
18 W	2400 lm	3000 K	1531 mm	2004.4886
26 W	3900 lm	4000 K	1531 mm	2004.4895
26 W	3700 lm	3000 K	1531 mm	2004.4892


\* Other lengths for luminaires with continuous diffuser via channel lighting system



### SUSPENSION SET PURELITE SLIM

Length 1500 mm, with wire suspension and self-lock, load max. 20 kg, mounting recommendation: every 1.5 m

Notes	Ref. n°
2 wire cords, can be clipped into place, with 2 m power feed cable, transparent, with cable clamp	2004.4908
1 wire cord, can be clipped into place, adjustable	2004.4079



### MOUNTING SPRING KIT PURELITE SLIM

made of spring steel, to facilitate mounting the support profile on the ceiling, to compensate for uneven surfaces, as a placeholder for cable routing, Recommended: all 1.5 m

Notes	Ref. n°
1 piece	2004.1005