



Giro

Ceiling mounted luminaire

With its remarkable elegance, the GIRO ring luminaire integrates seamlessly into Regent's clear and simple design language and amazes with its perfectly illuminated circle throughout. High-quality, curved aluminium, precisely crafted down to the last detail, forms the impressive design. The diffuser, made from a round extruded profile, not only results in an uninterrupted, trouble-free light pattern, but is also manufactured in a particularly resource-friendly way. The innovative bendable and integrated control gear is housed in the luminaire and results in a pure, perfect, round light.

FEATURES

High quality and seamless welded aluminum housing

Cover in polycarbonate (PC)

Control gear always integrated in the luminaire

Diffuser with only one cutting edge

Harmonious size ratio of diameter to luminaire housing

Direct and indirect light controllable together

Easy assembly without access to the electrical insert

SPECIFICATIONS

Height 77 mm / Width 60 mm

indirect-direct light emission or direct only

Dimmable digital DALI

Housing colours: white, black, silver

Driver always integrated in the luminaire

Opal diffuser

Also available as pendant luminaire


FIELDS OF APPLICATION

Office & Education: meeting rooms, offices, cafeterias, foyers and lobbies, corridors, staircases


Retail & Hospitality: hotels, reception areas, circulation zones

Giro


WHITE




A



B



C



D



E



F




G


Article number	Info	Colour / Finish	Diameter	
GIRO CM750 LED7700-830 DIR WH DALI 2008.3163	7700 lm 3000 K warm white	white	750	A, D, E
GIRO CM750 LED8100-840 DIR WH DALI 2008.3267	8100 lm 4000 K neutral white	white	750	A, D, E
GIRO CM1200 LED13400-830 DIR WH DALI 2008.3357	13400 lm 3000 K warm white	white	1200	B, D, F
GIRO CM1200 LED14100-840 DIR WH DALI 2008.3359	14100 lm 4000 K neutral white	white	1200	B, D, F
GIRO CM1500 LED15700-830 DIR WH DALI 2008.3378	15700 lm 3000 K warm white	white	1500	C, D, G
GIRO CM1500 LED16500-840 DIR WH DALI 2008.3383	16500 lm 4000 K neutral white	white	1500	C, D, G

Giro


SILVER




A



B



C




D



E



F



G

Article number	Info	Colour / Finish	Diameter	
GIRO CM750 LED7700-830 DIR SR DALI 2008.2490	7700 lm 3000 K warm white	silver	750	A, D, E
GIRO CM750 LED8100-840 DIR SR DALI 2008.3008	8100 lm 4000 K neutral white	silver	750	A, D, E
GIRO CM1200 LED13400-830 DIR SR DALI 2008.3344	13400 lm 3000 K warm white	silver	1200	B, D, F
GIRO CM1200 LED14100-840 DIR SR DALI 2008.3346	14100 lm 4000 K neutral white	silver	1200	B, D, F
GIRO CM1500 LED15700-830 DIR SR DALI 2008.3361	15700 lm 3000 K warm white	silver	1500	C, D, G
GIRO CM1500 LED16500-840 DIR SR DALI 2008.3367	16500 lm 4000 K neutral white	silver	1500	C, D, G

Giro

BLACK


230V




IP40

IK06


650°C




A



B



C



D



E



F



G

Article number	Info	Colour / Finish	Diameter	
GIRO CM750 LED7700-830 DIR BK DALI 2008.3155	7700 lm 3000 K warm white	black	750	A, D, E
GIRO CM750 LED8100-840 DIR BK DALI 2008.3161	8100 lm 4000 K neutral white	black	750	A, D, E
GIRO CM1200 LED13400-830 DIR BK DALI 2008.3349	13400 lm 3000 K warm white	black	1200	B, D, F
GIRO CM1200 LED14100-840 DIR BK DALI 2008.3353	14100 lm 4000 K neutral white	black	1200	B, D, F
GIRO CM1500 LED15700-830 DIR BK DALI 2008.3370	15700 lm 3000 K warm white	black	1500	C, D, G
GIRO CM1500 LED16500-840 DIR BK DALI 2008.3374	16500 lm 4000 K neutral white	black	1500	C, D, G