



PURELITE SLIM OFFICE

PURELITE SLIM is something to admire before it has even been turned on. The slimmest and thinnest luminaire in the industry, it is a feat of imagination and innovation. But then a switch is flicked. And PURELITE SLIM becomes a sleek strip of pure, uninterrupted, exceptional light. Although its design is hard to comprehend, the luminaire itself is easy to install at every stage of a project. So, the possibilities are as wide as PURELITE SLIM is so elegantly thin.

FEATURES

- Shadow-free lines of light, incl. illumination of the ceiling, timeless design
- Simple to integrate into the architecture thanks to its ultra-flat design: height of only 35 mm incl. control gear
- Available with integrated RUN diffuser (PURELITE SLIM D) or office-compatible RUN+ diffuser (PURELITE SLIM)
- Omnidirectional, with illumination of the ceiling, also available with direct lighting
- Batten luminaire range with a 2.5 cm design from standard, enables wall-to-wall planning

TECHNICAL DATA

Luminous flux of luminaire	1600-3100 lm, Office 2150 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index (CRI)	≥ 80
Maintained luminous flux	L80 75'000 h
Glare value	Up to UGR < 19 $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$
Protection class	I
Ingress Protection	IP20
Photobiological safety	risk group 0, no risk

SPECIFICATIONS

- Recessed ceiling, ceiling and wall mounting, pendant luminaire and channel lighting system
- Extremely good homogeneous direct illumination and all-round illumination
- support profiles made of natural anodised aluminium
- Clip-in LED batten with integrated through-wiring for quick and easy mounting
- LED batten luminaire replaceable on site
- High luminous efficacy of up to 150 lm/W

APPLICATION AREAS



Office & Education: open-plan offices, individual offices, classrooms, meeting rooms, foyers and lobbies, circulation zones

Retail & Hospitality: hotels, restaurants

Home & Living




IP20 230V IK08 $\varnothing_{0.5m}$ 850°C **A+**



CEILING MOUNTED LUMINAIRE PURELITE SLIM

System power	Luminous flux of luminaire	Colour temperature	Length	Glare value	Ref. n°
12 W	1340 lm	4000 K	781 mm	UGR < 19	2004.4899
12 W	1280 lm	3000 K	781 mm	UGR < 19	2004.4896
17 W	2150 lm	4000 K	1231 mm	UGR < 19	2004.4900
17 W	2050 lm	3000 K	1231 mm	UGR < 19	2004.4897
21 W	2700 lm	4000 K	1531 mm	UGR < 19	2004.4901
21 W	2550 lm	3000 K	1531 mm	UGR < 19	2004.4898


* Other lengths for luminaires with continuous diffuser via channel lighting system



SUSPENSION SET PURELITE SLIM

Length 1500 mm, with wire suspension and self-lock, load max. 20 kg, mounting recommendation: every 1.5 m

Notes	Ref. n°
2 wire cords, can be clipped into place, with 2 m power feed cable, transparent, with cable clamp	2004.4908
1 wire cord, can be clipped into place, adjustable	2004.4079



MOUNTING SPRING KIT PURELITE SLIM

made of spring steel, to facilitate mounting the support profile on the ceiling, to compensate for uneven surfaces, as a placeholder for cable routing, Recommended: all 1.5 m

Notes	Ref. n°
1 piece	2004.1005