



# Torus

## Ceiling mounted luminaire

TORUS is a vision coming to life. While it fascinates with a graceful and elaborate look, the organic, annular shape makes the luminaire suitable for countless architectural styles. It all started with the architects' exceptional idea to combine direct and indirect lighting components in one luminaire. So, our experienced specialists listened and made it happen. They realised TORUS with fascinating speed and precision and have developed its unique lighting characteristics providing an enhanced spatial experience in any room. TORUS can be placed almost everywhere and in various settings: a row of luminaires in a hallway for gentle guidance, a single luminaire to highlight the entrance of your flat or a group of luminaires creating enchanting atmospheres in a restaurant. TORUS is an unconventional beauty. An accomplished fusion of style and function.

### FEATURES

- Unique geometry in torus shape

---

- High-quality workmanship

---

- Direct and indirect light can be controlled separately

---

- Direct light for normative lighting in transition zones

---

- Indirect light for ceiling illumination

---

### TECHNICAL DATA

- System power: 36 W

---

- Luminous flux of luminaire: 3450 lm / 3650 lm

---

- Colour temperature: 3000 K / 4000 K

---

- Colour rendering index: CRI > 90

---

- Maintained luminous flux: L80 50'000 h

---

- Protection class: Protection class I

---

- Ingress Protection (IP): IP40

---

### SPECIFICATIONS

- Also available as pendant luminaire

---

- Colour temperatures: 3000 K, 4000 K

---

- Total 3000 lm

---

- Digital controllable via DALI

---

### FIELDS OF APPLICATION

- Fields of application

---

- Retail & Hospitality: retail spaces, living spaces, hotels, circulation zones

---

- Office & Education: meeting rooms, offices, cafeterias, foyers and lobbies, corridors

---

# Torus

230V




IP40


650°C



A



B



C

Article number	Info	Light control	
TORUS CW510 LED3450-930 DID DALI 2008.7970	3450 lm 3000 K warm white	DALI2	A, B, C
TORUS CW510 LED3450-930 DID MYLR 2008.7973	3450 lm 3000 K warm white	MyLights Remote Casambi	A, B, C
TORUS CW510 LED3650-940 DID DALI 2008.7972	3650 lm 4000 K neutral white	DALI2	A, B, C
TORUS CW510 LED3650-940 DID MYLR 2008.7974	3650 lm 4000 K neutral white	MyLights Remote Casambi	A, B, C