



Splash Clear

Damp-proof diffuser luminaire

Splash meets all the expectations for a professional dampproof diffuser luminaire. The variant furnished with stainless steel brackets and made from impact-resistant and UV-stabilised polycarbonate is highly durable, completely leakproof, and, being the "clear" version with transparent casing, guarantees a high-quality appearance. The measurable reduction of maintenance and energy cost are also highly commendable.

FEATURES

Meets all requirements for a damp-proof diffuser luminaire

IP66 protection rating – high protection against dust, dirt and moisture

Homogenous lighting through primary diffuser for an even spread of light

High luminous flux of luminaire of up to 8100 lm

High luminous efficacy of up to 150 lm/W

Aluminium heat sink for optimum thermal management

Robust and impact resistant, up to IK10

Operating temperature range –20 to +50 °C

Maintained luminous flux up to L90 71'000h / L80 145'000h

Robustness and transparent aesthetics

SPECIFICATIONS

For mounting on ceilings, walls and track, and for pendant mounting

Operating temperature range –20 to +40 °C

Bowl and diffuser made of polycarbonate (PC), transparent

Colour temperatures: 3000 K, 4000 K

Beam angle: wide

Integrated control gear Multilumen ON/OFF or dimmable digital DALI2

Available with integral through-wiring

Available with emergency unit

FIELDS OF APPLICATION

Industry: production and assembly plants, storage halls, cold storage facilities, exhibition halls, multi-storey car parks, loading zones, basements

Splash Clear

230V





IP66

IK10

850°C



0.5m



Article number	Info	Length	Beam spread characteristics	Light control	Through-wiring	emergency unit	
SPLASH CLR 1272 LED3700-4600-830 WB PC ONF E3h M 2008.9125	4600 lm 3000 K warm white	1272 mm	wide beam	ON/OFF		with emergency unit	A, B, C
SPLASH CLR 1272 LED3700-6200-830 WB PC ONF ML 2008.9123	6200 lm 3000 K warm white	1272 mm	wide beam	ON/OFF		without emergency unit	A, B, C
SPLASH CLR 1272 LED3900-4850-840 WB PC ONF E3h M 2008.9128	4850 lm 4000 K neutral white	1272 mm	wide beam	ON/OFF		with emergency unit	A, B, C
SPLASH CLR 1272 LED3900-6600-840 WB PC ONF ML 2008.9126	6600 lm 4000 K neutral white	1272 mm	wide beam	ON/OFF		without emergency unit	A, B, C
SPLASH CLR 1272 LED4600-830 WB PC DALI 2008.9129	4600 lm 3000 K warm white	1272 mm	wide beam	DALI2		without emergency unit	A, B, C
SPLASH CLR 1272 LED4850-840 WB PC DALI 2008.9132	4850 lm 4000 K neutral white	1272 mm	wide beam	DALI2		without emergency unit	A, B, C
SPLASH CLR 1572 LED4550-5700-830 WB PC ONF E3h M 2008.9154	5700 lm 3000 K warm white	1572 mm	wide beam	ON/OFF		with emergency unit	A, B, C
SPLASH CLR 1572 LED4550-7700-830 WB PC ONF ML 2008.9153	7700 lm 3000 K warm white	1572 mm	wide beam	ON/OFF		without emergency unit	A, B, C
SPLASH CLR 1572 LED4800-6000-840 WB PC ONF E3h M 2008.9156	6000 lm 4000 K neutral white	1572 mm	wide beam	ON/OFF		with emergency unit	A, B, C
SPLASH CLR 1572 LED4800-8100-840 WB PC ONF ML 2008.9155	8100 lm 4000 K neutral white	1572 mm	wide beam	ON/OFF		without emergency unit	A, B, C
SPLASH CLR 1572 LED6000-840 WB PC DALI 2008.9157	6000 lm 4000 K neutral white	1572 mm	wide beam	DALI2		without emergency unit	A, B, C
SPLASH CLR 1572 LED8100-840 WB PC DALI 2008.9159	8100 lm 4000 K neutral white	1572 mm	wide beam	DALI2		without emergency unit	A, B, C