



NEO / NEO+

Unlock the power within



PEOPLE LIGHT OUR WAY

NEO / NEO+

Ready for your bright future.

Break out of the usual lighting matrix and enter a completely new dimension of light. Awaken your room from the darkness and let yourself be seduced by the choice between **NEO** and **NEO+**.

Both versions always guarantee standard-compliant lighting for office environments. With **NEO+** you achieve the highest level of glare control: With a luminance of less than 1,500 cd/m², NEO+ is the ideal choice for particularly demanding visual tasks. Thanks to the integrated MDA 3.0 module, **NEO** and **NEO+** are ready for the IoT solution MyData Analysis and regent.cloud as standard.



Maximum glare control

NEO has a UGR of less than 10 and luminance levels of less than 3,000 cd/m², creating a pleasant working atmosphere without annoying glare. The **NEO+** version with impressive luminance levels of less than 1,500 cd/m² sets new standards in glare-free lighting.

Asymmetrical light distribution

With their asymmetrical light distribution, **NEO** and **NEO+** provide optimum light for an efficient working environment - unpleasant glare is avoided.

Simple assembly

The lamp head and base plate can be mounted quickly and easily with just four pre-assembled screws. **NEO** and **NEO+** are available with either a U or T base to suit any desk.


Single-user detection

Ideal for single workstations as well as for double workstations. Thanks to two separate motion sensors, **NEO / NEO+** always detects the ideal area.

MyData Analysis 3.0 (MDA 3.0)

Luminaire infrastructure as a data source: Our optional smart building system offers new possibilities for building management and helps to optimise space utilisation and operating costs in your company.



read the full story:



NEO / NEO+

Product range overview

NEO	NEO+
Luminous flux of luminaire / Lux	
12'200 lm / 12'800 lm	
Luminance	
< 3'000cd/m ²	< 1'500cd/m ²
Colour temperature	
3'000 K, 4'000 K	
Colour renderings	
Ra ≥80	
Efficiency	
Up to 162 lm/W	158 lm/W
Foot plates	
U- or T-Fuss	
Housing colours	
White, black, silver	
Light control	
1- or 2-channel	2-channel
Web-App Flash MyLight	
MyData Analysis und ALONEatWORK®	



For more information, please visit www.regent.ch/en/neo
#peoplelightourway



Subject to technical modifications.
Regent assumes no liability for printing errors.