



## Neo / Neo+ Office

### Freestanding luminaire

Break out of the ordinary lighting matrix and enter a whole new dimension of light. Awaken your space from darkness and be seduced by the choice between NEO and NEO+. Both guarantee standard-compliant lighting for office environments. With NEO+, you achieve the highest level of glare control: With a luminance of less than 1'500cd/m<sup>2</sup>, NEO+ is the ideal choice for particularly demanding visual tasks. Choose your path with the striking U-foot or the solid T-foot and anchor your lighting world firmly in reality. NEO is equipped for the future. Thanks to MDA 3.0 on board, the luminaire is already prepared for the IoT solution MyData Analysis. Immerse yourself in a world of light that will change you. NEO - the key to your illuminated future.

#### FEATURES

Free-standing design luminaire with microprismatic CLD+ optics, suitable for application in offices for perfect glare control

High luminous efficacy of up to 162 lm/W

Configuration possible via «Flash MyLight» web app

Smart lighting technology: ALONE at WORK®

#### SPECIFICATIONS

Luminous flux of luminaire 12'200 lm / 12'800 lm

Direct-indirect light emission [17%/83%]

Height: 2000 mm

Colour temperatures: 3000 K, 4000 K

Housing colours: white, black, silver

Operating unit integrated

#### FIELDS OF APPLICATION

Office & Education: offices, open-plan offices, Homeoffice, staff training facilities, meeting rooms, reception rooms, waiting rooms, libraries

# Neo / Neo+ Office


NEO OFFICE ≤ 3000 CD/M²

230V




IP20


650°C




A




B



C



D



E



F



G



H



I



J



K



L



M



N

Article number	Info	Colour / Finish	base plate	Control element	☒	☒
NEO T LED12200-830 BK 0IF CH 2010.0481	12200 lm 3000 K warm white	black	base plate, T-shaped	without control element	A, B, F	I
NEO T LED12200-830 BK 0IF EU 2010.0482	12200 lm 3000 K warm white	black	base plate, T-shaped	without control element	A, B, F	I
NEO T LED12200-830 BK 1FIC CH 2010.0489	12200 lm 3000 K warm white	black	base plate, T-shaped	with control element (1-channel) on the rod	A, D, J	I
NEO T LED12200-830 BK 1FIC EU 2010.0490	12200 lm 3000 K warm white	black	base plate, T-shaped	with control element (1-channel) on the rod	A, D, J	I
NEO T LED12200-830 BK 1F2C CH 2010.0497	12200 lm 3000 K warm white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, D, M	I
NEO T LED12200-830 BK 1F2C EU 2010.0498	12200 lm 3000 K warm white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, D, M	I
NEO T LED12200-830 SR 0IF CH 2010.0449	12200 lm 3000 K warm white	silver	base plate, T-shaped	without control element	A, B, G	I
NEO T LED12200-830 SR 0IF EU 2010.0450	12200 lm 3000 K warm white	silver	base plate, T-shaped	without control element	A, B, G	I
NEO T LED12200-830 SR 1FIC CH 2010.0457	12200 lm 3000 K warm white	silver	base plate, T-shaped	with control element (1-channel) on the rod	A, D, I	I
NEO T LED12200-830 SR 1FIC EU 2010.0458	12200 lm 3000 K warm white	silver	base plate, T-shaped	with control element (1-channel) on the rod	A, D, I	I
NEO T LED12200-830 SR 1F2C CH 2010.0465	12200 lm 3000 K warm white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, D, L	I
NEO T LED12200-830 SR 1F2C EU 2010.0466	12200 lm 3000 K warm white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, D, L	I
NEO T LED12200-830 WH 0IF CH 2010.0417	12200 lm 3000 K warm white	white	base plate, T-shaped	without control element	A, B, N	I
NEO T LED12200-830 WH 0IF EU 2010.0418	12200 lm 3000 K warm white	white	base plate, T-shaped	without control element	A, B, N	I
NEO T LED12200-830 WH 1FIC CH 2010.0425	12200 lm 3000 K warm white	white	base plate, T-shaped	with control element (1-channel) on the rod	A, D, H	I
NEO T LED12200-830 WH 1FIC EU 2010.0426	12200 lm 3000 K warm white	white	base plate, T-shaped	with control element (1-channel) on the rod	A, D, H	I
NEO T LED12200-830 WH 1F2C CH 2010.0433	12200 lm 3000 K warm white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, D, K	I
NEO T LED12200-830 WH 1F2C EU 2010.0434	12200 lm 3000 K warm white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, D, K	I
NEO T LED12800-840 BK 0IF CH 2010.0485	12800 lm 4000 K neutral white	black	base plate, T-shaped	without control element	A, B, G	I
NEO T LED12800-840 BK 0IF EU 2010.0486	12800 lm 4000 K neutral white	black	base plate, T-shaped	without control element	A, B, G	I
NEO T LED12800-840 BK 1FIC CH 2010.0493	12800 lm 4000 K neutral white	black	base plate, T-shaped	with control element (1-channel) on the rod	A, D, J	I
NEO T LED12800-840 BK 1FIC EU 2010.0494	12800 lm 4000 K neutral white	black	base plate, T-shaped	with control element (1-channel) on the rod	A, D, J	I
NEO T LED12800-840 BK 1F2C CH 2010.0501	12800 lm 4000 K neutral white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, D, M	I
NEO T LED12800-840 BK 1F2C EU 2010.0502	12800 lm 4000 K neutral white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, D, M	I
NEO T LED12800-840 SR 0IF CH 2010.0453	12800 lm 4000 K neutral white	silver	base plate, T-shaped	without control element	A, B, F	I

NEO T LED12800-840 SR 01F EU 2010.0454	12800 lm 4000 K neutral white	silver	base plate, T-shaped	without control element	A, B, F	1
NEO T LED12800-840 SR 1F1C CH 2010.0461	12800 lm 4000 K neutral white	silver	base plate, T-shaped	with control element (1-channel) on the rod	A, D, I	1
NEO T LED12800-840 SR 1F1C EU 2010.0462	12800 lm 4000 K neutral white	silver	base plate, T-shaped	with control element (1-channel) on the rod	A, D, I	1
NEO T LED12800-840 SR 1F2C CH 2010.0469	12800 lm 4000 K neutral white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, D, L	1
NEO T LED12800-840 SR 1F2C EU 2010.0470	12800 lm 4000 K neutral white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, D, L	1
NEO T LED12800-840 WH 01F CH 2010.0421	12800 lm 4000 K neutral white	white	base plate, T-shaped	without control element	A, B, N	1
NEO T LED12800-840 WH 01F EU 2010.0422	12800 lm 4000 K neutral white	white	base plate, T-shaped	without control element	A, B, N	1
NEO T LED12800-840 WH 1F1C CH 2010.0429	12800 lm 4000 K neutral white	white	base plate, T-shaped	with control element (1-channel) on the rod	A, D, H	1
NEO T LED12800-840 WH 1F1C EU 2010.0430	12800 lm 4000 K neutral white	white	base plate, T-shaped	with control element (1-channel) on the rod	A, D, H	1
NEO T LED12800-840 WH 1F2C CH 2010.0437	12800 lm 4000 K neutral white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, D, K	1
NEO T LED12800-840 WH 1F2C EU 2010.0438	12800 lm 4000 K neutral white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, D, K	1
NEO U LED12200-830 BK 01F CH 2010.0479	12200 lm 3000 K warm white	black	base plate, U-shaped	without control element	A, C, F	1
NEO U LED12200-830 BK 01F EU 2010.0480	12200 lm 3000 K warm white	black	base plate, U-shaped	without control element	A, C, F	1
NEO U LED12200-830 BK 1F1C CH 2010.0487	12200 lm 3000 K warm white	black	base plate, U-shaped	with control element (1-channel) on the rod	A, E, J	1
NEO U LED12200-830 BK 1F1C EU 2010.0488	12200 lm 3000 K warm white	black	base plate, U-shaped	with control element (1-channel) on the rod	A, E, J	1
NEO U LED12200-830 BK 1F2C CH 2010.0495	12200 lm 3000 K warm white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, E, M	1
NEO U LED12200-830 BK 1F2C EU 2010.0496	12200 lm 3000 K warm white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, E, M	1
NEO U LED12200-830 SR 01F CH 2010.0447	12200 lm 3000 K warm white	silver	base plate, U-shaped	without control element	A, C, G	1
NEO U LED12200-830 SR 01F EU 2010.0448	12200 lm 3000 K warm white	silver	base plate, U-shaped	without control element	A, C, G	1
NEO U LED12200-830 SR 1F1C CH 2010.0455	12200 lm 3000 K warm white	silver	base plate, U-shaped	with control element (1-channel) on the rod	A, E, I	1
NEO U LED12200-830 SR 1F1C EU 2010.0456	12200 lm 3000 K warm white	silver	base plate, U-shaped	with control element (1-channel) on the rod	A, E, I	1
NEO U LED12200-830 SR 1F2C CH 2010.0463	12200 lm 3000 K warm white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, E, L	1
NEO U LED12200-830 SR 1F2C EU 2010.0464	12200 lm 3000 K warm white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, E, L	1
NEO U LED12200-830 WH 01F CH 2010.0415	12200 lm 3000 K warm white	white	base plate, U-shaped	without control element	A, C, N	1
NEO U LED12200-830 WH 01F EU 2010.0416	12200 lm 3000 K warm white	white	base plate, U-shaped	without control element	A, C, N	1
NEO U LED12200-830 WH 1F1C CH 2010.0423	12200 lm 3000 K warm white	white	base plate, U-shaped	with control element (1-channel) on the rod	A, E, H	1
NEO U LED12200-830 WH 1F1C EU 2010.0424	12200 lm 3000 K warm white	white	base plate, U-shaped	with control element (1-channel) on the rod	A, E, H	1
NEO U LED12200-830 WH 1F2C CH 2010.0431	12200 lm 3000 K warm white	white	base plate, U-shaped	with control element (2-channel) on the rod	A, E, K	1
NEO U LED12200-830 WH 1F2C EU 2010.0432	12200 lm 3000 K warm white	white	base plate, U-shaped	with control element (2-channel) on the rod	A, E, K	1
NEO U LED12800-840 BK 01F CH 2010.0483	12800 lm 4000 K neutral white	black	base plate, U-shaped	without control element	A, C, G	1
NEO U LED12800-840 BK 01F EU 2010.0484	12800 lm 4000 K neutral white	black	base plate, U-shaped	without control element	A, C, G	1
NEO U LED12800-840 BK 1F1C CH 2010.0491	12800 lm 4000 K neutral white	black	base plate, U-shaped	with control element (1-channel) on the rod	A, E, J	1
NEO U LED12800-840 BK 1F1C EU 2010.0492	12800 lm 4000 K neutral white	black	base plate, U-shaped	with control element (1-channel) on the rod	A, E, J	1
NEO U LED12800-840 BK 1F2C CH 2010.0499	12800 lm 4000 K neutral white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, E, M	1
NEO U LED12800-840 BK 1F2C EU 2010.0500	12800 lm 4000 K neutral white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, E, M	1
NEO U LED12800-840 SR 01F CH 2010.0451	12800 lm 4000 K neutral white	silver	base plate, U-shaped	without control element	A, C, F	1
NEO U LED12800-840 SR 01F EU 2010.0452	12800 lm 4000 K neutral white	silver	base plate, U-shaped	without control element	A, C, F	1
NEO U LED12800-840 SR 1F1C CH 2010.0459	12800 lm 4000 K neutral white	silver	base plate, U-shaped	with control element (1-channel) on the rod	A, E, I	1
NEO U LED12800-840 SR 1F1C EU 2010.0460	12800 lm 4000 K neutral white	silver	base plate, U-shaped	with control element (1-channel) on the rod	A, E, I	1
NEO U LED12800-840 SR 1F2C CH 2010.0467	12800 lm 4000 K neutral white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, E, L	1
NEO U LED12800-840 SR 1F2C EU 2010.0468	12800 lm 4000 K neutral white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, E, L	1

NEO U LED12800-840 WH 0IF CH 2010.0419	12800 lm 4000 K neutral white	white	base plate, U-shaped without control element	A, C, N 1
NEO U LED12800-840 WH 0IF EU 2010.0420	12800 lm 4000 K neutral white	white	base plate, U-shaped without control element	A, C, N 1
NEO U LED12800-840 WH IF1C CH 2010.0427	12800 lm 4000 K neutral white	white	base plate, U-shaped with control element (1-channel) on the rod	A, E, H 1
NEO U LED12800-840 WH IF1C EU 2010.0428	12800 lm 4000 K neutral white	white	base plate, U-shaped with control element (1-channel) on the rod	A, E, H 1
NEO U LED12800-840 WH IF2C CH 2010.0435	12800 lm 4000 K neutral white	white	base plate, U-shaped with control element (2-channel) on the rod	A, E, K 1
NEO U LED12800-840 WH IF2C EU 2010.0436	12800 lm 4000 K neutral white	white	base plate, U-shaped with control element (2-channel) on the rod	A, E, K 1

# Neo / Neo+ Office


NEO+ OFFICE ≤ 1500 CD/M²

230V




IP20


650°C



A



B



C



D



E



F

Article number	Info	Colour / Finish	base plate	Control element	☒ ☒
NEO+ T LEDI2200-830 BK IF2C CH 2010.0473	12200 lm 3000 K warm white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, B, F 1
NEO+ T LEDI2200-830 BK IF2C EU 2010.0474	12200 lm 3000 K warm white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, B, F 1
NEO+ T LEDI2200-830 SR IF2C CH 2010.0441	12200 lm 3000 K warm white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, B, E 1
NEO+ T LEDI2200-830 SR IF2C EU 2010.0442	12200 lm 3000 K warm white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, B, E 1
NEO+ T LEDI2200-830 WH IF2C CH 2010.0409	12200 lm 3000 K warm white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, B, D 1
NEO+ T LEDI2200-830 WH IF2C EU 2010.0410	12200 lm 3000 K warm white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, B, D 1
NEO+ T LEDI2800-840 BK IF2C CH 2010.0477	12800 lm 4000 K neutral white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, B, F 1
NEO+ T LEDI2800-840 BK IF2C EU 2010.0478	12800 lm 4000 K neutral white	black	base plate, T-shaped	with control element (2-channel) on the rod	A, B, F 1
NEO+ T LEDI2800-840 SR IF2C CH 2010.0445	12800 lm 4000 K neutral white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, B, E 1
NEO+ T LEDI2800-840 SR IF2C EU 2010.0446	12800 lm 4000 K neutral white	silver	base plate, T-shaped	with control element (2-channel) on the rod	A, B, E 1
NEO+ T LEDI2800-840 WH IF2C CH 2010.0413	12800 lm 4000 K neutral white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, B, D 1
NEO+ T LEDI2800-840 WH IF2C EU 2010.0414	12800 lm 4000 K neutral white	white	base plate, T-shaped	with control element (2-channel) on the rod	A, B, D 1
NEO+ U LEDI2200-830 BK IF2C CH 2010.0471	12200 lm 3000 K warm white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, C, F 1
NEO+ U LEDI2200-830 BK IF2C EU 2010.0472	12200 lm 3000 K warm white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, C, F 1
NEO+ U LEDI2200-830 SR IF2C CH 2010.0439	12200 lm 3000 K warm white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, C, E 1
NEO+ U LEDI2200-830 SR IF2C EU 2010.0440	12200 lm 3000 K warm white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, C, E 1
NEO+ U LEDI2200-830 WH IF2C CH 2010.0407	12200 lm 3000 K warm white	white	base plate, U-shaped	with control element (2-channel) on the rod	A, C, D 1
NEO+ U LEDI2200-830 WH IF2C EU 2010.0408	12200 lm 3000 K warm white	white	base plate, U-shaped	with control element (2-channel) on the rod	A, C, D 1
NEO+ U LEDI2800-840 BK IF2C CH 2010.0475	12800 lm 4000 K neutral white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, C, F 1
NEO+ U LEDI2800-840 BK IF2C EU 2010.0476	12800 lm 4000 K neutral white	black	base plate, U-shaped	with control element (2-channel) on the rod	A, C, F 1
NEO+ U LEDI2800-840 SR IF2C CH 2010.0443	12800 lm 4000 K neutral white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, C, E 1
NEO+ U LEDI2800-840 SR IF2C EU 2010.0444	12800 lm 4000 K neutral white	silver	base plate, U-shaped	with control element (2-channel) on the rod	A, C, E 1
NEO+ U LEDI2800-840 WH IF2C CH 2010.0411	12800 lm 4000 K neutral white	white	base plate, U-shaped	with control element (2-channel) on the rod	A, C, D 1
NEO+ U LEDI2800-840 WH IF2C EU 2010.0412	12800 lm 4000 K neutral white	white	base plate, U-shaped	with control element (2-channel) on the rod	A, C, D 1

## Accessories Neo / Neo+ Office

1



**2010.1880**

EQP COMMOD AAW NEO

Communication module Neo

IP20

L = 145 mm, B = 39 mm, H = 42 mm