



Efficient,
pleasant light.

Echo 172

It is a well-known fact that all good things come from above. This is particularly true for Echo. Regent's new downlight is a delight even before being switched on. The installation of the lightweight is a matter of seconds and feasible completely tool-free. The luminance of Echo is positively influenced by both

mixing chamber and diffusion disc. The result: a pleasantly soft lighting experience which even sensitive eyes will find enjoyable, yet without compromising efficiency.

FEATURES

Glare-free light thanks to highly precise light conduction
High luminous efficiency
Passive cooling
Quick and tool-free mounting
Lightweight system suitable for all ceiling types
Streamlined design makes for perfect integration into ceiling architecture
Lightweight system suitable for all ceiling types

TECHNICAL DATA

System power	19 W, 25 W
Luminous flux of luminaire	1700 lm, 1800 lm, 1900 lm, 2000 lm, 2200 lm, 2350 lm, 2500 lm, 2600 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index (CRI)	R _a ≥ 90
Maintained luminous flux	L90 (B50) 50'000 h
Protection class	I
Ingress Protection	IP20/IP44 from below when mounted in closed ceilings

SPECIFICATIONS

Downlight with pleasantly homogeneous luminance levels
Ceiling cut out 172 mm
Aluminium-coated or white reflector
Tool-free assembly of accessories
DALI light control
Operating unit included in delivery

APPLICATION AREAS

Retail & Hospitality: retail spaces, presentation of merchandise/key locations, restaurants, hotels, art & culture establishments







IP20
IP44

230V



0.5m

850°C


A

B

C
RECESSED DOWNLIGHT ECHO 172 LED

System power	Luminous flux of luminaire	Colour temperature	Notes	Emergency unit	Ref. n°
19 W	2000 lm	4000 K	reflector silver		A 1023.4159
19 W	1900 lm	3000 K	reflector silver		A 1023.4135
19 W	1800 lm	4000 K	reflector white		B 1023.4155
19 W	1700 lm	3000 K	reflector white		B 1023.4131
19 W	2000 lm	4000 K	reflector silver	with emergency unit	A 1023.4171
19 W	1900 lm	3000 K	reflector silver	with emergency unit	A 1023.4147
19 W	1800 lm	4000 K	reflector white	with emergency unit	B 1023.4167
19 W	1700 lm	3000 K	reflector white	with emergency unit	B 1023.4143
19 W	2000 lm	4000 K	reflector silver		C 1023.4163
19 W	1900 lm	3000 K	reflector silver		C 1023.4139
19 W	2000 lm	4000 K	reflector silver	with emergency unit	C 1023.4175
19 W	1900 lm	3000 K	reflector silver	with emergency unit	C 1023.4151
25 W	2600 lm	4000 K	reflector silver		A 1023.4160
25 W	2500 lm	3000 K	reflector silver		A 1023.4136
25 W	2350 lm	4000 K	reflector white		B 1023.4156
25 W	2200 lm	3000 K	reflector white		B 1023.4132
25 W	2600 lm	4000 K	reflector silver	with emergency unit	A 1023.4172
25 W	2500 lm	3000 K	reflector silver	with emergency unit	A 1023.4148
25 W	2350 lm	4000 K	reflector white	with emergency unit	B 1023.4168
25 W	2200 lm	3000 K	reflector white	with emergency unit	B 1023.4144
25 W	2600 lm	4000 K	reflector silver		C 1023.4164
25 W	2500 lm	3000 K	reflector silver		C 1023.4140
25 W	2600 lm	4000 K	reflector silver	with emergency unit	C 1023.4176
25 W	2500 lm	3000 K	reflector silver	with emergency unit	C 1023.4152


COVER RING ECHO 172 LED

clear

Farbe	Notes	Ref. n°
white	IP44 from below, in case of closed ceilings	1023.4544
silver	IP44 from below, in case of closed ceilings	1023.4541
white	IP55 from below, in case of closed ceilings	1023.4540
silver	IP55 from below, in case of closed ceilings	1023.4539


COVER RING ECHO 172 LED

matt

Farbe	Notes	Ref. n°
white	IP55 from below, in case of closed ceilings	1023.4538
silver	IP55 from below, in case of closed ceilings	1023.4535


RING ECHO 172 LED

Notes	Ref. n°
	1023.4534


EMBEDDING HOUSING B.BOX

Notes	Ref. n°
	2000.9153