



Viva

Recessed downlight

The VIVA recessed LED downlight – a small downlight with a large light package. Now newly available as a DALI version. It's the perfect combination – maximum efficiency meets minimum installation mass with extremely attractive value for money.

FEATURES

Small, compact, efficient, flat

High luminous efficacy of up to 133 lm/W

Easy to mount

1 size – 2 power outputs: 8 W, 12 W

IP54 protection rating

TECHNICAL DATA

System power: 8 W / 12 W

Luminous flux of luminaire: 1070 lm / 1020 lm / 1600 lm / 1520 lm

Colour temperature: 4000 K / 3000 K

Colour rendering index: CRI > 80

Maintained luminous flux: L70 50'000 h

Protection class: Protection class I

Ingress Protection (IP): IP44 / IP20 / IP54

SPECIFICATIONS

Operating unit integrated

ON/OFF or dimmable digital DALI

White, rotationally symmetric, with cover frame

Opal cover glass

Passive cooling

FIELDS OF APPLICATION

Fields of application

Office & Education: reception rooms

Retail & Hospitality: lobbies, hotels, corridors, staircases

Viva

230V



IP44

IK08

650°C




0.5m




IP20
IP54



A



B




C



Article number	Info	Light control		
VIVA DL CR155 LED1020-830 105 WH DALI 2009.2338	1020 lm 3000 K warm white	DALI	A, B, C	1
VIVA DL CR155 LED1020-830 105 WH ONF 2009.2334	1020 lm 3000 K warm white	ON/OFF	A, B, C	1
VIVA DL CR155 LED1070-840 105 WH DALI 2009.2339	1070 lm 4000 K neutral white	DALI	A, B, C	1
VIVA DL CR155 LED1070-840 105 WH ONF 2009.2335	1070 lm 4000 K neutral white	ON/OFF	A, B, C	1
VIVA DL CR155 LED1520-830 105 WH DALI 2009.2340	1520 lm 3000 K warm white	DALI	A, B, C	1
VIVA DL CR155 LED1520-830 105 WH ONF 2009.2336	1520 lm 3000 K warm white	ON/OFF	A, B, C	1
VIVA DL CR155 LED1600-840 105 WH DALI 2009.2341	1600 lm 4000 K neutral white	DALI	A, B, C	1
VIVA DL CR155 LED1600-840 105 WH ONF 2009.2337	1600 lm 4000 K neutral white	ON/OFF	A, B, C	1

1



1001.6973

BOX EQP CNCREHOUSING ST RND-157

Embedding housing B.Box for fairced concrete, in steel, sendzimized, round,

opening \varnothing = 157 mm, EL = 315 mm, EB = 315 mm, ET = 120 mm,

Material

steel

Colour / Finish

sendzimized

Recessed length

315

Recessed depth

120

Weight

2.45