



Matrix

Whether in a shop, museum or exhibition – light has a considerable influence on what your customers decide to buy. But the Matrix LED spotlight not only guarantees first-class lighting for the presentation of your display; its pared-down design also fits in harmoniously with your presentation concept. All this with outstanding efficiency values thanks to low maintenance costs.

Perfect in design
and technology

FEATURES

- High luminous efficiency
- Excellent colour rendering: CRI ≥ 90
- Wide coverage of Track spotlight: 360° rotation, 45°/90°/45° extended vertical tilt
- Reflectors can be exchanged without tools

TECHNICAL DATA

System power	22 W, 26 W, 32 W
Luminous flux of luminaire	2750 lm, 3100 lm, 3250 lm, 4500 lm, 4750 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index (CRI)	$R_a \geq 90$
Maintained luminous flux	L80 (B50) 50'000h
Protection class	I
Ingress Protection	IP20

SPECIFICATIONS





- High-quality die-cast aluminium housing
- Pure aluminium reflector
- ON/OFF or DALI
- Beam angles: 20°, 30°, 40°
- Housing colours: white, silver
- With conductor track adaptor for Global Trac Pro (ON/OFF) and Global Trac Pulse (DALI)

APPLICATION AREAS

Retail & Hospitality: retail spaces, exhibition spaces, museums, art & culture establishments, presentation of merchandise/key locations



IP20 650°C 230V $\varnothing 0.5m$


A

B

C

TRACK SPOTLIGHT MATRIX LED

System power	Luminous flux of luminaire	Colour temperature	Colour	Light control	Ref. n°
22 W	2900 lm	4000 K	white	ON/OFF	A 2000.8804
22 W	2900 lm	4000 K	white	DALI	A 2003.2210
22 W	2750 lm	3000 K	white	ON/OFF	A 2000.8789
22 W	2750 lm	3000 K	white	DALI	A 2003.2204
22 W	2900 lm	4000 K	silver	ON/OFF	A 2000.8795
22 W	2900 lm	4000 K	silver	DALI	A 2003.2207
22 W	2750 lm	3000 K	silver	ON/OFF	A 2000.8776
22 W	2750 lm	3000 K	silver	DALI	A 2003.2201
26 W	3250 lm	4000 K	white	ON/OFF	A 2000.8862
26 W	3250 lm	4000 K	white	DALI	A 2003.2228
26 W	3100 lm	3000 K	white	ON/OFF	A 2000.8846
26 W	3100 lm	3000 K	white	DALI	A 2003.2219
26 W	3250 lm	4000 K	silver	ON/OFF	A 2000.8853
26 W	3250 lm	4000 K	silver	DALI	A 2003.2223
26 W	3100 lm	3000 K	silver	ON/OFF	A 2000.8831
26 W	3100 lm	3000 K	silver	DALI	A 2003.2213
32 W	4750 lm	4000 K	white	ON/OFF	A 2000.8992
32 W	4750 lm	4000 K	white	DALI	A 2003.2240
32 W	4500 lm	3000 K	white	ON/OFF	A 2000.8979
32 W	4500 lm	3000 K	white	DALI	A 2003.2234
32 W	4750 lm	4000 K	silver	ON/OFF	A 2000.8985
32 W	4750 lm	4000 K	silver	DALI	A 2003.2237
32 W	4500 lm	3000 K	silver	ON/OFF	A 2001.1870
32 W	4500 lm	3000 K	silver	DALI	A 2003.2231
22 W	2900 lm	4000 K	white	ON/OFF	B 2000.8805
22 W	2900 lm	4000 K	white	DALI	B 2003.2211
22 W	2750 lm	3000 K	white	ON/OFF	B 2000.8790
22 W	2750 lm	3000 K	white	DALI	B 2003.2205
22 W	2900 lm	4000 K	silver	ON/OFF	B 2000.8796
22 W	2900 lm	4000 K	silver	DALI	B 2003.2208
22 W	2750 lm	3000 K	silver	ON/OFF	B 2000.8778
22 W	2750 lm	3000 K	silver	DALI	B 2003.2202
26 W	3250 lm	4000 K	white	ON/OFF	B 2000.8863
26 W	3250 lm	4000 K	white	DALI	B 2003.2229
26 W	3100 lm	3000 K	white	ON/OFF	B 2000.8847
26 W	3100 lm	3000 K	white	DALI	B 2003.2220
26 W	3250 lm	4000 K	silver	ON/OFF	B 2000.8854
26 W	3250 lm	4000 K	silver	DALI	B 2003.2224
26 W	3100 lm	3000 K	silver	ON/OFF	B 2000.8832
26 W	3100 lm	3000 K	silver	DALI	B 2003.2215
32 W	4750 lm	4000 K	white	ON/OFF	B 2000.8993
32 W	4750 lm	4000 K	white	DALI	B 2003.2241


System power	Luminous flux of luminaire	Colour temperature	Colour	Light control	Ref. n°
32 W	4500 lm	3000 K	white	ON/OFF	B 2000.8980
32 W	4500 lm	3000 K	white	DALI	B 2003.2235
32 W	4750 lm	4000 K	silver	ON/OFF	B 2000.8986
32 W	4750 lm	4000 K	silver	DALI	B 2003.2238
32 W	4500 lm	3000 K	silver	ON/OFF	B 2000.8973
32 W	4500 lm	3000 K	silver	DALI	B 2003.2232
22 W	2900 lm	4000 K	white	ON/OFF	C 2000.8806
22 W	2900 lm	4000 K	white	DALI	C 2003.2212
22 W	2750 lm	3000 K	white	ON/OFF	C 2000.8791
22 W	2750 lm	3000 K	white	DALI	C 2003.2206
22 W	2900 lm	4000 K	silver	ON/OFF	C 2000.8797
22 W	2900 lm	4000 K	silver	DALI	C 2003.2209
22 W	2750 lm	3000 K	silver	ON/OFF	C 2000.8779
22 W	2750 lm	3000 K	silver	DALI	C 2003.2203
26 W	3250 lm	4000 K	white	ON/OFF	C 2000.8864
26 W	3250 lm	4000 K	white	DALI	C 2003.2230
26 W	3100 lm	3000 K	white	ON/OFF	C 2000.8848
26 W	3100 lm	3000 K	white	DALI	C 2003.2221
26 W	3250 lm	4000 K	silver	ON/OFF	C 2000.8855
26 W	3250 lm	4000 K	silver	DALI	C 2003.2226
26 W	3100 lm	3000 K	silver	ON/OFF	C 2000.8833
26 W	3100 lm	3000 K	silver	DALI	C 2003.2216
32 W	4750 lm	4000 K	white	ON/OFF	C 2000.8994
32 W	4750 lm	4000 K	white	DALI	C 2003.2242
32 W	4500 lm	3000 K	white	ON/OFF	C 2000.8981
32 W	4500 lm	3000 K	white	DALI	C 2003.2236
32 W	4750 lm	4000 K	silver	ON/OFF	C 2000.8987
32 W	4750 lm	4000 K	silver	DALI	C 2003.2239
32 W	4500 lm	3000 K	silver	ON/OFF	C 2000.8974
32 W	4500 lm	3000 K	silver	DALI	C 2003.2233



COVER SET MATRIX LED

acrylic glass

Notes	Ref. n°
	2000.3872



BARN DOORS SET MATRIX LED

black

Notes	Ref. n°
	1002.9253



REFLECTOR SET MATRIX LED

Notes	Ref. n°
Flood 40°	1002.9412
Medium 30°	1002.9414