



## Level CLD

Every range of luminaires aims to feature a clear and consistent formal language. The surface-mounted wall version of Level provides perfect interaction with the free-standing luminaire – guaranteeing the same design, the same materials and the same high-quality and highly efficient lighting. Just without a stand.

Maximum  
efficiency

### FEATURES

Microprismatic optics, suitable for application in offices
Direct-indirect light Emission (44%/56%)
UGR ≤ 16 especially suitable for demanding visual tasks (pursuant to SN EN 12464-1)
High luminous efficiency of up to 118 lm/W
CLD optics for an especially even spread of light
Frame in aluminium
High-quality design, frame just 42 mm deep

### TECHNICAL DATA

System power	40 W
Luminous flux of luminaire	5600 lm, 5900 lm
Colour temperature	3000 K, 4000 K
Colour Rendering Index (CRI)	Ra ≥ 80
Maintained luminous flux	L80 (B50) 50'000 h
Protection class	I
Ingress Protection	IP20
Photobiological safety	risk group 0, no risk

### SPECIFICATIONS



Colour: silver
ON/OFF or dimmable digital SensoDim
Operating unit integrated
Also available as freestanding luminaire and pendant luminaire

### APPLICATION AREAS

**Office & Education:** offices, staff training facilities, meeting rooms, reception rooms, waiting rooms, libraries



IP20 230V 650°C **A++**



#### WALL MOUNTED LUMINAIRE LEVEL CLD LED

System power	Luminous flux of luminaire	Colour temperature	Light control	Notes	Ref. n°
40 W	5900 lm	4000 K	DALI		2001.8922
40 W	5900 lm	4000 K	SensoDim®	with light/movement sensor	2001.8924
40 W	5600 lm	3000 K	DALI		2001.8921
40 W	5600 lm	3000 K	SensoDim®	with light/movement sensor	2001.8923