



FLOW TUBE

Minimalism perfected
all around.

PEOPLE LIGHT OUR WAY

FLOW TUBE

Well-rounded minimalism
for modern spaces.

FLOW TUBE – a light sculpture that impresses as a classic design element through the use of just one visible material, as made out of a single mould. With timeless elegance, its design seamlessly integrates into any setting, celebrating the essence of minimalism. The innovative Spread Light Applicator technology distributes the light evenly along the diffuser, like a flowing stream of light.

It turns spaces into immersive atmospheric environments through its balanced combination of direct and indirect lighting. **FLOW TUBE** highlights the high quality of light, where aesthetics and functionality merge into a harmonious unity.

Tunable White

FLOW TUBE allows for continuous dimming and offers colour temperatures from 2'700 K to 6'500 K. This allows precise adjustments to be made for a wide range of applications, from a cosy atmosphere to a productive working environment – the ideal lighting is always guaranteed.



Lighting for modern rooms

FLOW TUBE is versatile and can be used in a wide variety of settings. With its organic shape and elegant design it creates architectural focal points in a variety of spaces. Its application and design possibilities are unlimited, allowing it to fit effortlessly into the most diverse concepts.

Timeless

FLOW TUBE's timeless appeal lies in its perfect balance of form and function. It offers superior light quality while maintaining a discreet visual footprint. The luminaire's ability to blend direct and indirect lighting creates atmospheric environments, adapting effortlessly to changing design trends and user needs.

read the full story:





FLOW TUBE



Product range overview

Lengths
0,6 m, 0,9 m, 1,2 m, 1,5 m 2,4 m, 3,6 m or system
Luminous flux of luminaire
up to 2'050 lm / 1,2 m
Colour temperature
3'000 K, 4'000 K or Tunable White
Glare control
FLOW TUBE UGR < 19 at 1'540 lm / 1,2 m
FLOW UGR < 19 at 1'280 lm / 1,2 m
Mounting
Surface-mounted or rope suspension
Lighting control
DALI
Protection class
IP44

FLOW TUBE



FLOW



For more information, please visit www.regent.ch/en/flow-tube
#peoplelightourway



Subject to technical modifications.
Regent assumes no liability for printing errors.