



Tweak Essential Office

Freestanding luminaire

2004.7065

TWEAK2 ESS S1U1950 LED9400-840 WH 0IFSEDI EU



System power	68 W
Light control	SensoDim®
Colour temperature	4000 K neutral white
Colour / Finish	white
Luminous flux of luminaire	9400 lm
Weight	18.32 kg
Colour consistency SDCM	SDCM 3
Unified Glare Rating (UGR) C0	11
Colour Rendering Index (CRI)	CRI > 80
Unified Glare Rating (UGR) C90	11
Maintained luminous flux	L80 50'000 h

Freestanding luminaire Tweak Essential Office single head face side, with LED, system power: 68 W, luminous flux of luminaire 9400 lm, standby power 0.5 W, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax >= 65° <= 3000 cd/m²), Photobiological safety: Safe., 230 V, direct-indirect light emission, 19%/81%, common dimmable and switchable, without control element, luminaire head 2x90°adjustable, one-piece housing in die-cast aluminium, white, RAL 9016, thermo painted, office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, with interface module/switch on the base plate, 1 integral control gear, SensoDim®, with light/movement sensor, base plate, U-shaped, 2m power supply cable with IEC 7/7 european plug,

ingress protection IP20, protection class I, glow wire test 650 °C, this product contains a light source of energy efficiency class C, and EPREL registration number: 1140598,

L = 734 mm, B = 215 mm, total height = 1950 mm

Datasheet : Accessories

Tweak Essential Office - Freestanding luminaire

2004.7065

TWEAK2 ESS S1U1950 LED9400-840 WH 01FSEDI EU



2004.4914

ALONE at WORK

Communication module ALONE at WORK for freestanding uplighter Tweak