



Lightpad Tunable Office

Freestanding luminaire

2007.8308

LGTPD4 L1L LED7200-9TW WH 1IF1315 AAW EU



System power	66 W
Light control	SensoDim® + ALONE at WORK®
Colour temperature	6500 K Tunable White
Colour / Finish	white
Luminous flux of luminaire	7200 lm
Weight	20.939 kg
Colour consistency SDCM	SDCM 3
Unified Glare Rating (UGR) C0	13
Colour Rendering Index (CRI)	CRI > 90
Unified Glare Rating (UGR) C90	16
Maintained luminous flux	L90 50'000 h

Freestanding luminaire Lightpad Tunable Office for single person workstation, left, with LED, system power: 66 W, standby power 1 W, luminous flux of luminaire 7200 lm, colour rendering index CRI > 90, colour temperature 2700 - 6500 K, Tunable White, colour tolerances SDCM 3, lifetime LED L90 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax >= 65° <= 3000 cd/m²), Photobiological safety: Safe., 230 V, direct-indirect light emission, with 1 higher control element, in aluminium, white, RAL 9016, 2 integral control gears, SensoDim® + ALONE at WORK®, with light/movement sensor, 3m power supply cable with IEC 7/7 european plug, base plate, full mould, oblong, ENEC certified,

protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1258598

lower edge of control element 1315 mm, L = 782 mm, B = 275 mm, total height = 2000 mm