



Act

Pendant luminaire

2003.2290

ACT SM PEN100-2200 LED4030-830 DID WH TCH1-10V



System power	43 W
Light control	dimnable digital TouchDim + 1-10V
Colour temperature	3000 K warm white
Colour / Finish	white
Luminous flux of luminaire	4030 lm
Weight	1.877 kg
Colour consistency SDCM	SDCM 3
Unified Glare Rating (UGR) C0	19
Colour Rendering Index (CRI)	CRI > 80
Unified Glare Rating (UGR) C90	19
Maintained luminous flux	L70 50'000 h

Pendant luminaire Act for surface mounting, with LED, system power: 43 W, luminous flux of luminaire 4030 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L70 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 0.19 A, direct-indirect light emission, (52%/48%), housing in aluminium, white, 1 integral control gear, dimmable digital TouchDim + 1-10V, wide beam,

protection class I, ingress protection IP20, glow wire test 850 °C, this product contains a light source of energy efficiency class E and EPREL registration number: 850933

Ø = 100 mm, H = 160 mm, p = 2200 mm